

Classic Wood Stove

F1100, F2400, F3100



F2400 with black legs, gold accent door, convector airmate and bottom heat shield.

The timeless styling of the Classic Wood Stove comes in three sizes producing from 55,000 to 80,000 BTU of toasty warmth for a single living area or an entire home. Up to 77% efficiency means any room can be heated quickly. It also means your wood stove burns cleanly meeting the strictest air quality standards set by DEQ Washington Phase II Clean Air Standard of 4.5 grams/hr. or less.



F2400 with black door and pedestal.



F2400 with black door, brushed nickel legs, convector airmate and bottom heat shield.



F2400 with gold door, gold legs, convector airmate and bottom heat shield.



Standard Features

- ◆ EPA Certified
- ◆ Mobile home and alcove approved
- ◆ Closest clearances in the industry
- ◆ Single rod draft control
- ◆ Brick-lined firebox
- ◆ Airwash system
- ◆ Rear heat deflector

Optional Features

- ◆ Cast iron door in gold, black**, gold accent or nickel accent
- ◆ Cast iron legs in gold, black or brushed nickel
- ◆ Pedestal base
- ◆ Bottom heat shield (when using legs)
- ◆ Ash drawer
- ◆ 2-speed blower
- ◆ Convector airmate
- ◆ Outside air kit
- ◆ Screen door

Specifications

| | F1100 | F2400 | F3100 |
|------------------------|-------------|-------------|--------------|
| Maximum BTU* | 55,000 | 75,000 | 80,000 |
| Typical Sq. Ft. Heated | 600-1200 | 1000-2200 | 2000-3500 |
| Efficiency | 77.7% | 77.0% | 75.4% |
| Maximum Log Size | 18" | 18" | 21" |
| Burn Time (typical)* | up to 8 hrs | up to 8 hrs | up to 10 hrs |
| Emissions (grams/hr) | 3.0g | 3.4g | 4.2g |
| Firebox Size | 1.4 cu. ft. | 2.3 cu. ft. | 2.9 cu. ft. |
| Flue Size | 6" | 6" | 6" |

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Black doors come with nickel handles & nickel hinge caps