

Classic I2400 & I3100

Medium & Large Wood Insert



Regency I2400 with nickel accent door, nickel convection grills, regular faceplate and blower.

Your open masonry fireplace can allow as much as 90% of your fire's heat to escape out the chimney. By adding a Regency Classic Fireplace Insert, you will keep the heat in your home. Regency Inserts are ready to install and fit easily into your existing fireplace. Increase the value of your home and decrease your monthly heating bill.



I2400 with black door, nickel convection grills, black faceplate trim and blower.



I2400 with gold door, gold convection grills, regular faceplate, brass faceplate trim and blower.



I2400 with gold accent door, gold convection grills, brass faceplate trim and blower.



Standard Features

- ◆ EPA Certified
- ◆ Single rod draft control
- ◆ Airwash system
- ◆ Brick-lined fire box
- ◆ Black convection grills
- ◆ Mobile home approved (I2400 only)

Optional Features

- ◆ Cast iron door in gold, black**, gold accent or nickel accent
- ◆ Gold or nickel convection grills
- ◆ Regular or oversize faceplate (black trim included)
- ◆ Screen door
- ◆ Brass faceplate trim
- ◆ Regency stainless steel flex liner kit
- ◆ 2-speed blower

Specifications

	I2400	I3100
Maximum BTU*	75,000	80,000
Typical Sq. Ft. Heated	1000-2000	1800-3000
Optimum Efficiency	77.0%	75.4%
Maximum Log Size	18"	21"
Burn Time (Typical)*	up to 8 hrs	up to 10 hrs
Emissions (grams/hr)	3.4g	4.2g
Firebox Size	2.3 cu. ft.	2.9 cu. ft.
Flue Size	6"	6"

Minimum Fireplace Opening

	I2400	I3100
Width	25"	28"
Height	21-1/2"	25"
Depth	17"	17"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Black doors come with nickel handles & nickel hinge caps